

Range Name:
Borough Place Brick

Ref: P+E-BPB-TDS-01
Technical specification of dry pressed ceramic wall tiles manufactured in accordance with the EN 14411 standard, BIII group.

	Testing To Standard	Average Typical Values	Result
Physical Properties			
Group			BIII
Values According To			PN-EN 14411:2016
Material			Ceramic
Colours			White
Finish			Gloss, Matt, Bumpy
Size Formats (mm)	100 x 100, 150 x 150, 200 x 100, 300 x 100, 200 x 200, 200 x 250, 200 x 300, 250 x 400		
Thickness (mm)			Mixed
Rectified			No
Shade Variation			V1
Technical Properties			
Dimensions and Surface Aspect	UNE-EN-ISO 10545-2	Requested Value	Complies
Water Absorption	UNE-EN-ISO 10545-3	Eb >10%	15% μ'
Modulus of Rupture	UNE-EN-ISO 10545-4	≥ 15 N/mm²	25 N/mm² μ'
Breaking Strength	UNE-EN-ISO 10545-4	≥ 200N	480 μ'
Cracking Resistance	UNE-EN-ISO 10545-11	Declared Value	Complies
Chemical Resistance Properties			
Household Chemicals & Pool Salts	UNE-EN-ISO 10545-13	Declared Value	GA
Low Concentration Acids & Alkalis	UNE-EN-ISO 10545-13	Declared Value	GLA
High Concentration Acids & Alkalis	UNE-EN-ISO 10545-13	Declared Value	GHA
Stain Resistance Properties			
Stain Resistance	UNE-EN-ISO 10545-14	Min Class 5	Class 5
MOHS	EN 101:1991	Declared Value	3.5-5

